

X-Form WB

Liquid emulsion chemical form release agent

Product Description

X-Form WB is a form release agent for all types of formwork used in concrete construction.

Composition

X-Form WB consists of a non-hazardous emulsified release agent, wetting additives and a rust inhibitor.

Advantages

- Meets LEED VOC Limits
- Formaldehyde free
- Easy to use
- Can be used on steel, timber and plywood
- Reduces blow holes
- Non-staining
- Environmentally responsible
- Does not affect subsequent finishes applied to the concrete

Uses

- Release agent for all types of formwork
- Can be used for autoclave curing
- Can be used with white concrete
- Ready mix trucks to prevent cement build up

Specification Compliance

LEED NC2009 IEQ 4.2

Volatile Organic Content

VOC = <10 g/L

Coverage

20 to 40m² per liter.

Packaging

20 and 200 liter drums.

Shelf Life

24 months when stored below 35C under shade in a dry environment. Drums to be rolled for 5 mins prior to use.

Installation Guidelines

Application

Roll drum before use.

X-Form WB should be sprayed onto the formwork using a knapsack unit at a uniform rate of between 20 to 40m² per liter depending on the porosity and texture of the

mould surface. The nozzle of the spray head should be set to produce a fine, even mist. On small sections of the formwork, the product may be applied using a paint brush or roller. Avoid ponding and remove excess material with a dry cloth or sponge.

Apply X-Form WB before the first casting and between subsequent castings, preferably immediately after stripping and cleaning the mould. This should take place as close as possible to the next use of the formwork to avoid dust and airborne contaminants settling on the prepared formwork. Timber moulds will progressively improve in performance as they become impregnated with the release agent.

Limitations

Avoid excessive application

Avoid skin contact

Do not discard into the water system

Health and Safety

This product is for industrial use only by trained operatives. It is potentially hazardous if not used correctly. Please refer to the Material Safety Data Sheet (MSDS) prior to the purchase and use of this product. The MSDS can be obtained via our website www.ncc.com.eg.

Authorized Technical Specialist

Please note that only NCC X-Calibur Authorized Technical Specialists ('ATs') are permitted to change any of the information in this data sheet or to provide written recommendations concerning the use of this product. Visit www.ncc.com.eg for a full list of NCC X-Calibur ATs.

Datasheet Validity

NCC X-Calibur makes modifications to its product datasheets on a continuous basis. Check the current datasheet section on www.ncc.com.eg to ensure you have the latest version.

Warranties

NCC X-Calibur supplies products that comply with the properties shown on the current datasheets. In the unlikely event that products supplied are proved not to comply with these properties, then we will replace the non-compliant product or refund the purchase price. NCC X-Calibur does not warrant or guarantee the installation of the products as it does not have control over the installation or end use of the products. Any suspected defects must be reported to NCC X-Calibur in writing within five working days of being detected. NCC X-Calibur Construction Chemistry Inc. **makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied.** NCC X-Calibur Construction Chemistry Inc. shall not be liable for damages of any sort including remote or consequential damages, down time, or delay.